



Date 10/18/2023 Quote no. NOTX2019000445N971 Your ref.

NATLG/NORTRUX LEASING INC 18110 118 AVE NW EDMONTON T5S 2G2 AB

Technical Specification

ANTHEM 64T SLEEPER 70INCH

CUSTOMER/VEHICLE INFO

CANADA - WARRANTY REGISTRATION LOCATION

RAPID QUOTE MANAGEMENT PROGRAM - CANADA

CANADA LEASING PROGRAM

ANTHEM 64T SLEEPER 70INCH

DEALER FLEET WITH LESS THAN 25 VEHICLES IN OWN FLEET OF ANY VEHICLE BRAND

RETAIL OR STOCK - CUSTOM SPECIFICATIONS

COMMERCIAL

CANADA, CARB ENGINE EMISSION (US17 / US21 / ZERO EMISSION)

Made in Macungie, PA USA

ENGLISH

B-TRAIN TANKER TRAILERS

LESS THAN ONE DELIVERY OR PICK-UP OF GOODS EVERY 50KM

2021 MODEL YEAR

144,000 LB (65 TONNES) GROSS COMBINATION WEIGHT

GRADES <6% GREATER THAN 98% OF DRIVING DISTANCE MAX GRADE 16%

AMBIENT TEMPERATURE HOT. WARMER THAN 104 F (40 C) ALLOWED UP TO 25 HOURS PER YEAR

ON HIGHWAY, STARTING GRADES<16%

BRAKE REGULATION, STOPPING DISTANCE 76M (250FT)

CONCRETE LOADING AND / OR UNLOADING SURFACE

LINEHAUL / LONG HAUL SERVICE





ENGINE/TRANSMISSIONS

MP8-505C MACK 505HP @ 1500-1700 RPM (PEAK) 1950 RPM (GOV) 1860 LB-FT, US'21 (ON-HWY ONLY)

BASIC, GEAR-SELECTION TUNING

GREEN HOUSE GAS HIGHWAY APPLICATION

MACK TMD13AFO-HD mDRIVE HD 13 SP, CREEPER/ MULTI-SPEED REVERSE (OVERDRIVE)

WITHOUT 12TH GEARBOX GEAR LOCK-OUT

EXHAUST/EMISSIONS

IDLE EMISSION CERTIFICATION, CARB (WITH DECAL LOCATED ON LOWER LH CORNER / DRIVER DOOR

CLEARTECH ONE BOX E.A.T.S. RH SIDE UNDER CAB US17 / US21

DUAL VERTICAL INBOARD MOUNTED STRAIGHT EXHAUST STACK TURNED OUT

12' 6" FROM GROUND

DUAL, BRIGHT FINISH HEAT SHIELDS, STACKS, ELBOWS AND SCR COVER (IF EQUIPPED)

18.4 GALLON (70 L) 26" LEFT SIDE FRAME MOUNTED

WITHOUT DEF TANK VENTILATION FILTER

EMISSION OBD, DISPLAY ONLY, USA2020





ENGINE EQUIPMENT

UNDER HOOD SINGLE ELEMENT DRY TYPE W/AIR INTAKE FROM BOTH SIDES OF HOOD BLACK ALUMINUM MOUNTED BEHIND GRILLE AND WINTER FRONT COVER STANDARD FUEL FILTER POSITION

DELCO 12V 165A (36SI) BRUSHLESS W/ REMOTE VOLTAGE SENSING

(4) MACK 12V 730/2920 CCA DEEP CYCLE THREADED STUD TYPE

ETHYLENE GLYCOL FULLY FORMULATED COOLANT (50/50 MIX DYED PINK) TO -34DEG, W/ FILTER

KYSOR FAN, "ON-OFF", W/MANUAL ENGAGEMENT SWITCH

MACK MP8 POWERLEASH

DAVCO 382, (FLUID HTD) FUEL HEATER/WATER SEPARATOR W/VENDOR PRIMARY FLAMING RIVER BIG SWITCH WIRED TO POSITIVE SIDE

LH RAIL UNDER CAB, PARALLEL TO FRAME W/STEPS, W/AIR RESERVOIR MOUNTED BELOW (4 BATTERY MAX)

FLAMING RIVER BIG SWITCH WIRED TO POSITIVE SIDE

POLISHED ALUMINUM

INTEGRATED LOW VOLTAGE DISCONNECT

MACK EPDM RADIATOR & HEATER HOSES

12 VOLT DELCO 39MT-MXT

OIL PAN

FURNISH CAP RETAINER FOR OIL FILL & RADIATOR OVERFLOW TANK

WITHOUT ENGINE STOP. EMERGENCY

12v ELECTRIC STARTING AID + 120v 1500w BLOCK HEATER + 120v 150w OIL PAN HEATER VEHICLE AND TRAILER (IF APPLICABLE) STOP LAMPS ACTIVATE UPON SERVICE BRAKE APPLICATION ONLY(3899000)

CLUTCH/TRANS EQUIPMENT

MACK mDRIVE-PREMIUM SHIFTER

ZF/SACHS SINGLE PLATE 17" (430MM) ORGANIC MATERIAL

SPICER SPL350HDXL "EXTENDED LUBE SERIES" (PROPS2XL)

SPICER SPL250HDXL EXTENDED LUBE SERIES

75W - 90 (SYNTHETIC LUBRICANT)

MACK mDRIVE TRANSMISSION OIL COOLER MOUNTED LH SIDE OIL TO WATER COOLER

UNIVERSAL JOINT HALF-ROUND TYPE

TRANSMISSION OUTPUT TORQUE BASIC

HALF-ROUND UNIVERSAL JOINT







FRONT AXLE EQUIPMENT

FRONT STABILIZER BAR

14600# (6600 KG) MACK FXL14.6 STRAIGHT SPINDLE/UNITIZED BEARINGS

MACK TAPERLEAF 14600# (6600 KG) GROUND LOAD RATING, EQUAL BIAS

MERITOR EX+ AIR DISC BRAKES 430MM (17") L-TYPE

FRONT BRAKE DISC LIGHTWEIGHT

DUST SHIELDS FOR FRONT AXLE

AUTOMATIC FOR AIR DISC BRAKES

FRONT BRAKE CHAMBER MANUFACTURER, WABCO

BASIC HUB UNITIZED IRON, FRONT

TRW TAS66 INTEGRAL POWER

LUBRICATED SUSPENSION PINS AND BUSHINGS

REAR AXLE EQUIPMENT

46000# (20900kg) MERITOR RT46-160 (SINGLE REDUCTION) W/PDLO

W/O WIDE TRACK AXLE

LUBE PUMP AND FILTER

VENDOR CARRIER

3.73 RATIO

PAX 46 HIGH STABILITY HENDRICKSON PRIMAXX AIR (VENDOR AXLES ONLY)

60" AXLE SPACING (BOGIE WHEELBASE)

ELECTRICAL REGULATION LEVELING DEVICE

AIR SUSPENSION DUMP, SPEED LIMITED, WARNING INDICATOR & BUZZER

REAR SHOCK ABSORBER

TRANSVERSE TORQUE ROD - ALL AXLES

MERITOR - CAM 16.5"x8 5/8" Q+

AUX SPRING BRAKE QTY, 4 CHAMBERS

CAST IRON

REAR SPRING BRAKE CHAMBERS 30/30 TYPE

MERITOR - AUTOMATIC

DUST SHIELDS FOR REAR AXLE

ALUMINUM PRESET REAR HUB W/INTEGRATED SPINDLE NUT

POWER DIVIDER LOCKOUT, W/BUZZER & LIGHT

HALDEX GOLD SEAL (3" STROKE) BRAKE CHAMBERS

DRIVER CONTROLLED INTER WHEEL DIFFERENTIAL LOCK ALL RR.AXLES W/INDIVIDUAL SWITCHES

BENDIX SWITCHES AND VALVES WHERE POSSIBLE

FURNISH AUTOMATIC TRACTION CONTROL (ATC) FULL DISABLE SWITCH









FRAME EQUIPMENT/FUEL TANKS

248"

62"

STEEL - 300MM X 90MM X 9.5MM -- (11.81" X 3.54" X 0.37")

STANDARD 2 STEP CAB ACCESS

STEEL

POLISHED ALUMINUM

BOXED AND TAPERED CROSSMEMBER

TAPERED AND FLANGED RAIL ENDS (28 deg.)

BETTS B60S (ANGLED) STAINLESS STL W/INTGRTD REFLECTIVE TAPE

AERODYNAMIC, PAINTED, WITH BLACK ACCENT

SKID PLATE UNDER BUMPER AND RADIATOR

SKID PLATE UNDER BUMPER AND RADIATOR

142 GALLON (540 L) 26" ALUMINUM ROUND

FURNISH ELECTRONIC FUEL LEVEL SENDER ILO MECH

142 GALLON (540 L) 26" ALUMINUM ROUND

BRAIDED HOSE

W/O FILLER NECK SCREEN

DUAL DRAW AND RETURN FUEL SYSTEM

BRIGHT FINISH ALUMINUM STEPS & STAINLESS STEEL BRIGHT FINISHED STRAPS

PLASTIC QUARTER FENDERS

AIR/BRAKE

MANUAL DRAIN VALVES, WITH LANYARDS ON ALL TANKS

ALUMINUM, POLISHED

W/O RELOCATION OPTION

TWO (2) VALVE DUAL BRAKE SYSTEM - TRAILER SUPPLY AND TRACTOR-TRAILER PARK W/O RELOCATED AIR TANKS

ELECTRICAL

ROOF LAMP, LED TYPE, NON SPECIFIED MANUFACTURER, RECTANG SEMI-FLUSH MODEL

ECCO BACK-UP ALARM 575 CONSTANT SOUND LEVEL 107 dB

FOG LAMPS (ROUND)

LED TYPE TAIL LAMP MODULE MTD BELOW REAR CROSSMEMBER

TWO (2) EXTRA DASH MOUNTED ILLUMINATED SWITCHES

DRL WHEN ENGINE RUNNING & PARK BRAKE OFF









TRAILER CONNECTIONS

AIR - HOLLAND FW35 ILS SERIES, LH RELEASE (AVAIL: 6.81",7.80",8.82",9.80")

SLIDING 5TH WHEEL MTG, 24" TRAVEL

STEEL FIFTH WHEEL ANGLES

5TH WHEEL ANGLE, 10MM THICKNESS

50" BOGIESPREAD = -5" OFFSET, 52" BS = -4", 54" BS = -3", 55" BS = -2.5"

BASIC RAMP

1295MM (51") GROUND TO 5TH WHEEL TOP HEIGHT

224MM (8.81"), FIFTH WHEEL LEG-HEIGHT (SELECTED BY KAX)

GLAD HAND COUPLINGS - NORTH AMERICAN STD

HAND CONTROL VALVE FOR TRAILER BRAKES W/ AIR CONNECTIONS OR SERVICE

BRAKES W/O AIR CONNECTIONS

TRAILER AIR BRAKE CONNECTIONS, BACK OF CAB

LOW PROFILE DECK PLATE

HOSE TENDER, POGO STICK (CHASSIS MOUNTED)

SINGLE, 7 PIN SAE HOT CENTER PIN, DASH MOUNTED SWITCH BATTERY FEED, BACK OF CAR

TRAILER AIR HOSES (12' NON-COILED TYPE)

SINGLE INCANDESCENT FLUSH MTD LOWER LHS & DUAL INCANDESCENT OUTBOARD MTD ON SIDE SHIELDS

ELECTRICAL PLUG HOLDER (INCLUDES GLAD HAND STORAGE)

TRAILER ELECTRICAL CORD (12' NON-COILED TYPE)

PTO

F1-81R PARKER PUMP/REAR OF mDRIVE TRANSMISSION

WITHOUT REAR ENGINE POWER TAKE OFF

PTO PUMP PROVISIONS FOR DIN 5462 W/DASH MTD SWITCH.

SPECIALTY EQUIPMENT

WITHOUT COLLISION WARNING SYSTEM

WITHOUT LANE DEPARTURE SYSTEM

WITHOUT AUXILIARY TRANSMISSION

W/O ON BOARD SCALES

W/O COLLISION WARNING SYSTEM

WITHOUT AUXILIARY POWER UNIT







CAB INTERIOR (A THRU G)

REAR AXLE OIL TEMP GAUGE IN DID (DRIVER INFORMATION DISPLAY)

AUX. INCAB PNEUMATIC LINE CLEANOUT

BLEND AIR HVAC W/"ATC" TEMP REGULATION

W/O OPTIONAL DASH MTD. LIGHT

RED FLOOR LIGHTING W/SWITCH PLUS (4) DOOR LAMPS W/SWITCHES

5LB (ABC RATED/AMEREX) MOUNTED BETWEEN LH SEAT BASE AND DOOR WITH VALVE AIMED REARWARD

2ND GA PKG W/ENG OIL TEMP, TRANS OIL TEMP, PYRO, BOOST PRESS

METRIC PREDOMINENT - ROADSPEED W/U.S. UNITS FOR ALL OTHER GAUGES

CAB INTERIOR (H THRU R)

DEFAULT: ENGLISH, SPANISH, FRENCH

AUTO SHUTOFF FOR RADIO ENTERTAINMENT SYSTEM WHEN VEHICLE IS ENGAGED IN REVERSE

SPEAKER LOC, ABOVE & IN DOORS, REAR WALL, SLEEPER, ADD. WOOFER & 50W, 2CH, AMPLIFER

ELECTRONIC KEYLESS ENTRY

2 POL, 304SS 3.5X15" W/SELF-ADH. BK; AT REC. SECTION CAB SILL PL. BELOW BOTH DRS PREMIUM STEREO, AM/FM, CD-PLAYER, MP3, WEATHER BAND, BLUETOOTH, SIRIUS/XM SATELLITE

48" ANTENNA RIGHT SIDE MIRROR MOUNTED

48" ANTENNA LEFT SIDE MIRROR MOUNTED

POWER LEADS (5-WAY BINDING POSTS FOR CB RADIO) IN HEADER CONSOLE

MOUNTING PLATE AND VELCRO STRAP IN HEADER CONSOLE

W/SLEEPER BOX FURNISH KIT MOUNTED LH LUGGAGE COMPARTMENT

ALL CHASSIS KEYED AT RANDOM





CAB INTERIOR (S THRU Z)

MACK-AIR, HIGH BACK, W/ ADJ AIR SHOCKS, 4 CHAMBER AIR LUMBAR, BOLSTER, EXTENSION, W/ HEAT

DRIVER'S SEAT - STEEL GREY ULTRA-LEATHER

MACK-AIR, HIGH BACK, W/ ADJ AIR SHOCKS, 4 CHAMBER AIR LUMBAR, BOLSTER, EXTENSION, W/ HEAT

PASSENGER'S SEAT - STEEL GREY ULTRA-LEATHER

INBOARD MOUNTED ARM REST, DRIVER'S & RIDER'S SEAT

LAP & SHOULDER (BOTH SEATS) CAB MOUNTED SHOULDER BELT ADJUSTMENT (NOT AVAIL W/EXTENDED RIDER SEAT)

PREMIUM PACKAGE, STEEL GRAY (Package 12A)

SEAT BELT REMINDER IN INSTRUMENT, WITH AUDIO

SEAT, DUST COVER FOR DRIVER'S AND RIDER'S SEATS

KEY TYPE

2 SPOKE LEATHER GRIP, SATIN ALUMINUM SPOKES, WITH SWITCHES

TINTED WINDSHIELD & SIDE WINDOWS

2-PIECE WINDSHIELD

2 SPEED ELECTRIC MOTOR W/INTERMITTENT FEATURE

CAB - SLEEPER BOX

70" STANDUP SLEEPER

STORAGE BIN ABOVE DOORS, BOTH SIDES

UPPER REAR WALL CABINET AND LOWER SHELF W/CUP HOLDERS

WITH BOTH WINDSHIELD/WINDOW AND SLEEPER BUNK CURTAINS

REFRIGERATOR 49L. MOUNTED IN CAB

120V/1800W INVERTER MOUNTED IN SLEEPER STORAGE COMPARTMENT, W/SHORE POWER, AND W/5 OUTLETS

SLEEPER BOX - DIGITAL ALARM CLOCK

LIFT-UP LOCKING LOWER BUNK WITH PREMIUM INNERSPRING MATRESS (39" X 80")

HEATER / AIR CONDITIONING FOR SLEEPER BOX

LUGGAGE COMPARTMENT LOCK OPTION, KEYED ALIKE KEY & LATCH HANDLE

LUGGAGE COMPARTMENT LID OPENING, BOTH SIDES

SLEEPER BOX - (2) 12 VOLT DC POWER OUTLETS

WEBASTO AUX CAB HEATER MODEL AIR TOP 2000 ST

SLEEPER BOX - TV ANTENNA AND 12V OUTLET FOR TV TRAY

BOTH SIDES SLEEPER BOX LOWER WINDOW, POP-OUT

LH BASE CABINET, SHELVES W/ DOOR, DRAWER, & SLIDE OUT WORK TABLE

LH UPPER WARDROBE CABINET, & TOP STORAGE

RH BASE CABINET, WITH REFRIGERATOR OR REFRIGERATOR PREP. & DRAWER

RH UPPER CABINET WITHOUT DOOR W/BEZEL & TOP STORAGE









CAB EXTERIOR

(1) BLACK TWIN TRUMPET, UNDER CAB MOUNTED

SINGLE TONE

WITHOUT CONVEX TYPE

AERO MIRROR - BODY COLOR, HEATED & MOTORIZED both sides, WIDE ANGLE both sides, W/O LAMPS

SUN VISOR, EXTERIOR, FIBERGLASS (PAINTED)

W/O MISC ORNAMENT CHANGE OPTION

PREMIUM BLACK EXTERIOR CAB GRAB HANDLE, BLACK GRAB HANDLE RH INTERIOR WINDSHIELD POST

AERODYNAMIC DEVICES

SIDE SHIELDS

WHEELS & TIRES

POLISHED ALUMINUM DISC - OUTBOARD OF DUAL WHEELS - CONCAVE SIDE 11R24.5 G MICHELIN XZE2 (13220 lbs)

24.5x8.25 ALCOA LVL ONE ALUM DISC, 10-HOLE HUB PILOTED, SEVERE SERVICE (11 1/4" 286mm BC), 5.06" INS

11R24.5 H MICHELIN X WORKS XDY (26440 lbs) (DRIVE ONLY)

24.5x8.25 ALCOA LVL ONE ALUM DISC, 10-HOLE HUB PILOTED, SEVERE SERVICE (11 1/4" 286mm BC), 6.60" OUT

WHEEL NUT BASIC FINISH, FRONT

WHEEL NUT BASIC FINISH, REAR

STANDARD VALVE STEMS AND CAPS

W/O HYDRAULIC JACK

COMMUNICATION SYSTEMS

CO-PILOT DISPLAY, DRIVER ACCESS LEVEL 1

TELEMATICS GATEWAY, 4G/LTE AND WLAN SYSTEM WITH DIAGNOSTIC SERVICES







ENGINE ELECTRONICS

WITHOUT ENGINE SOFTWARE SETTINGS

OIL PRESSURE, ENGINE SHUTDOWN

COOLANT TEMP, ENGINE SHUTDOWN

ENGINE PROTECTION (SHUTDOWN)

ENG FAN CONTROL, MOVING VEHICLE, TIME SETTING, 5 MIN

IDLE CONTROL, 650 RPM

INCREASE 15 MINUTE MAXIMUM TIME

IDLE SHUTDOWN ABS TAMPER CHECK, ENABLED

ENGINE IDLE COOLDOWN, DISABLE

ENGINE IDLE SHUTDOWN, DISABLE

38C DEG (100F), WARM UP TEMP DELAY

5 MIN. WARM UP TIME DELAY

ENG IDLE SHUTDOWN TIME OVERRIDDEN IF TORQUE > THAN LIMIT

IDLE SHUTDOWN OVERIDE UPTO 20% ENGINE LOAD THRESHOLD

AMBIENT TEMP MIN TRESHOLD, 16 DEG C, (60 DEG F)

AMBIENT TEMP MAX TRESHOLD, 27 DEG C, (80 DEG F)

ELECTRONIC HAND THROTTLE, MAX ROAD SPEED, 16 KMH (10 MPH)

ELECTRONIC HAND THROTTLE, MAX ENGINE SPEED, 2100 RPM

ELECTRONIC HAND THROTTLE, MIN ENGINE SPEED, 700 RPM

TRANSMISSION ELECTRONICS

W/O ELEC TRANS PACKAGE OPTION (all non-Allison transmissions)

W/O ALLISON FUELSENSE 2.0 PROGRAMMING

mDRIVE- HEAVY HAUL - ECON, PERF, PERF+, & HH DRIVE MODES, AUTO RETURN (premium)

ECONO ROLL DISABLE mDRIVE (REQUIRED FOR ALL OTHER TRANSMISSIONS)

MACKCELLERATOR ENABLE







VEHICLE ELECTRONICS

ACCELERATION LIMITING FEATURE, DISABLED

WITHOUT DRIVER PERFORMANCE PARAMETERS

DRIVER ID FUNCTION, DISABLED

ENGINE OVERSPEED, ALL CONDITIONS, TIME LOG IF ABOVE 2200 RPM

ENGINE OVERSPEED, FUELED, TIME LOG IF ABOVE 2100 RPM

VEHICLE OVERSPEED, ALL COND, TIME LOG IF ABOVE 75MPH (121KMH)

VEHICLE OVERSPEED, FUELED, TIME LOG IF ABOVE 70MPH (113KMH)

ENGINE IDLE DELAY TO START LOG, 2 MIN

PERIODIC TRIP LOG, DAY 1 OF THE MONTH

DETECTION OF SPEED SENSOR TAMPERING, ENABLE

ENG TORQUE LIMITED TO 50%, IF SPEED SENSOR TAMPER DETECTED

1950 MAXIMUM ENGINE SPEED AT 0 MPH

105 KM/H ROAD SPEED LIMITER(65 MPH)

105 KM/H PEDAL ROAD SPEED LIMITER (65MPH)

RSL CONTROL TYPE NORMAL

POWER DIVIDER LOCK OUT (PDLO) ROAD SPEED LIMIT 8KMH (5MPH)

MAX CRUISE, 105 KPH (65 MPH)

MIN CRUISE, 32 KPH (20 MPH)

CRUISE RESUME WITH CLUTCH

ENG BRK ENGAGE IN CRUISE, 3 MPH, ABOVE SET SPEED

CRUISE CONTROL

PTO ELECTRONICS

PTO 1ST, AUTO SET SINGLE SPEED, DISABLE

PTO 2ND, AUTO SET SINGLE SPEED, DISABLE

PTO1 FOR SPLITTER RANGE - KEYPAD REMOTE CONTROLLED

PTO2 FOR SPLITTER RANGE - KEYPAD REMOTE CONTROLLED





PAINT

SINGLE COLOR

METALLIC PAINT

BLACK METALLIC; P9085

NO SECOND TRUCK COLOR PROVIDED; NO COLOR

NO THIRD TRUCK COLOR PROVIDED; NO COLOR

PAINT - CAB, URETHANE CLEAR COAT

SAME AS FIRST COLOR - CAB

SAME AS FIRST COLOR - HOOD

SAME AS FIRST COLOR - SLEEPER ROOF

SAME AS FIRST COLOR - SUN VISOR

MACK BLACK (URETHANE)

SAME AS FIRST COLOR - MIRROR COVER

SAME AS FIRST COLOR - BUMPER

W/O OPTIONAL FUEL TANK PAINT

SAME AS CHASSIS RUNNING GEAR

SAME AS CHASSIS RUNNING GEAR

CALCULATED CODES - KAX

YES, THE ORDER MUST BE CALCULATED AUTOMATIC ROUTING & CLIPPING PLACEMENT, CENTER SECTION







BASE WARRANTY & PURCHASED COVERAGES

WITHOUT OMNITRACS FOR MACK TRUCKS

HEAVY DUTY WARRANTY CLASSIFICATION

HEAVY DUTY STANDARD BASE COVERAGE 12 MONTHS/100,000 MILES (161,000 KM)

MACK MP7/MP8 BASE ENGINE COVERAGE 24 MONTHS / 250,000 MILES (402,000KM)

US and CANADA EQUIPPED VEHICLE EMISSION COMPONENTS COVERAGE 60 MONTHS/100,000 MILES (161,000 KM)

W/O MACK ENGINE AFTERTREATMENT TREATMENT PROTECTION PLAN

36 MO/250K MI: STANDARD mDRIVE TRANSMISSIONS HEAVY DUTY WARRANTY

STANDARD VENDOR NORMAL / HEAVY DUTY COVERAGE 36 MONTHS/350,000 (563,00 KM)

AIR CONDITIONING STANDARD COVERAGE (Sealed System Only) 12 MONTHS UNLIMITED MILEAGE

STANDARD NORMAL / HEAVY DUTY CHASSIS TOWING 90 DAYS OR 5.000 MILES

STANDARD MACK ENGINE TOWING COVERAGE 24 MONTHS/250,000 MILES (402,000 KM)

W/O ALTERNATOR and STARTER EXTENDED WARRANTY COVERAGE

W/O STARTER PURCHASED COVERAGE

W/O ALTERNATOR PURCHASED COVERAGE

24 MONTH - GUARDDOG CONNECT WITH MACK OTA (with ASIST and Mack OneCall))

W/O TELEMATIC SERVICE PACKAGE

W/O PREMIUM MAINTENANCE PLAN

W/O AFTERTREATMENT PREMIUM MAINTENANCE PLAN

W/O PREMIUM MAINTENANCE - CHASSIS LUBE AND INSPECTION COVERAGE

W/O CUSTOM/BUNDLED PURCHASE COVERAGE OPTION

Customer Adaptation

KYSOR FAN, "ON-OFF", W/MANUAL ENGAGEMENT SWITCH 60" AXLE SPACING (BOGIE WHEELBASE)

Market Extras

21A Freight (28) 21A Material Surcharge CAN (28)

